

BINOPTIC 2 electronic tap

Ref. 383000

Mains, for slim panels, stopcock, L. 140mm

2026 UK public price excluding VAT: £422.46



DESCRIPTION

BINOPTIC 2 electronic tap - Ref. 383000

Satin finish electronic basin tap for slim panels:

230/6V mains supply.

Reduced-stagnation solenoid valve and electronic unit are integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant aerator.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).

Wall-mounted stainless steel tap.

Presence detection sensor at the end of the spout optimises detection.

Anti-blocking security.

Spout with smooth interior and low water volume (reduces bacterial development).

Set detection distance, duty flush and launch thermal shocks manually.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush



LED diagnostic aids

TECHNICAL CHARACTERISTICS

BINOPTIC 2 electronic tap - Ref. 383000

Supply	230/6V mains supply
Connector	M½"
Technology	Electronic
Spout length	140mm
Flow rate	3 lpm
Finish	Satin

Norms

ACS

Warranty

