

BINOPTIC MIX 2 electronic basin mixer

Ref. 482110

Mains, cross wall 100mm, L. 220mm

2024 UK public price excluding VAT: £492.01



DESCRIPTION

BINOPTIC MIX 2 electronic basin mixer - Ref. 482110

Cross wall chrome-plated electronic basin mixer:
230/6V mains supply.
Reduced-stagnation solenoid valve and electronic unit are integrated into the body of the mixer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant aerator.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Wall-mounted stainless steel mixer.
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Anti-blocking security.
Spout with smooth interior and low water volume (reduces bacterial development).
Side temperature control with adjustable maximum temperature limiter.
Set duty flush and launch thermal shocks manually.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Anti-bacterial proliferation duty flush



Sleek design

TECHNICAL CHARACTERISTICS

BINOPTIC MIX 2 electronic basin mixer - Ref. 482110

Supply	230/6V mains supply
Connector	F3/8"
Technology	Electronic
Spout length	220mm
Flow rate	3 lpm
Finish	Chrome-plated
Warranty	

