BIOFIL 3-month tap head filter

Ref. 20350

Sterile

2026 UK public price excluding VAT: **£114.56**



DESCRIPTION

BIOFIL 3-month tap head filter - Ref. 20350

DELABIE anti-Legionella and all-germ tap head filter.
Device made from ABS.
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
Qualified water volume per duration of use: 9,000 litres.
Filtration flow rate: 4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).
Space saving, suitable for taps with a low spout height: H. 50mm, Ø. 56mm
Controlled management of retro-contamination: protective skirt and angled connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 3 months after installation.
Resistance to thermal shocks: 70°C for 30 minutes.
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 3 hours (cumulative total).
Sterile filter. Individually wrapped, sterile.
CE Class Is medical device.
Single unit. Can only be ordered in multiples of 10.
Packaged in boxes of 10.

ADVANTAGES

- Anti-Legionella and all-germ
- Space saving
- Optimised position: angled connection
- Lifespan: 3 months after installation

TECHNICAL CHARACTERISTICS

BIOFIL 3-month tap head filter - Ref. 20350

Technology	Point-of-use filtration
Height	50mm
Flow rate	4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar
Diameter	56mm
Norms	ACS WRAS KTW BWGL CE

