

BIOFIL 3-month tap head filter

Ref. 20351

Sterile

2025 UK public price excluding VAT: £105.93



DESCRIPTION

BIOFIL 3-month tap head filter - Ref. 20351

DELABIE anti-Legionella and all-germ tap filter, laminar flow.
 Device made from ABS.
 Membrane type: tubular microfiltration.
 Membrane made from polyethylene.
 Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
 Qualified water volume per duration of use: 9,000 litres.
 Filtration flow rate: 4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).
 Space saving, suitable for taps with a low spout height: H. 50mm - Ø. 56mm.
 Controlled management of retro-contamination: protective skirt and angled connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste).
 Maximum upstream pressure at the point-of-use: 5 bar.
 Maximum lifespan: 3 months after installation.
 Resistance to thermal shocks: 70°C for 30 minutes.
 Resistance to chemical shocks: active chlorine levels up to 100 ppm for 3 hours (cumulative total).
 Sterile filter. Individually wrapped, sterile.
 CE Class Is medical device.
 Packaged individually. Must be ordered in quantities of 10. Packaged in boxes of 10 units.

TECHNICAL CHARACTERISTICS

BIOFIL 3-month tap head filter - Ref. 20351

Technology	Point-of-use filtration
Height	50mm
Flow rate	4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar
Diameter	56mm
Lifespan	3 months

Norms



ADVANTAGES

- Anti-Legionella and all-germ
- Space saving
- Optimised position: angled connection
- Lifespan: 3 months after installation

