

BINOPTIC 2 electronic tap

Ref. 374110E

Mains, deck-mounted, H. 170mm, Bluetooth®

2026 UK public price excluding VAT: £577.35



DESCRIPTION

BINOPTIC 2 electronic tap - Ref. 374110E

Deck-mounted satin electronic basin tap:

230/6V mains supply.

Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.

Scale-resistant aerator.

Adjustable duty flush (~60 seconds every 24 hours after the last use).

Stainless steel tap, 170mm high for semi-recessed basins.

Sensor at the end of the spout optimises detection.

PEX flexible with filter.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Spout with smooth interior and low water volume (reduces niches where bacteria can develop).

Set presence detection range, duty flush and launch thermal shocks manually.

Bluetooth® version: advanced settings and operating data download via

DELABIE Connect app.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC 2 electronic tap - Ref. 374110E

| | |
|-------------|-------------------------------|
| Supply | 230/6V mains supply |
| Connector | M3/8" |
| Technology | Electronic |
| Drop height | 170mm |
| Flow rate | 3 lpm |
| Finish | Chrome-plated |
| Norms | ACS |
| Warranty | 30 YEAR WARRANTY |

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush



Easy to configure & monitor operation

