

BIOFIL 4-month tap and wall shower filter

Ref. 20450

Sterile

2025 UK public price excluding VAT: £116.59



DESCRIPTION

BIOFIL 4-month tap and wall shower filter - Ref. 20450

DELABIE anti-Legionella and all-germ tap and wall-mounted shower filter, shower spray.

Device made from ABS.

Membrane type: tubular microfiltration.

Membrane made from polyethylene.

Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.

Qualified water volume per duration of use: 12,000 litres.

Filtration flow rate: 4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).

Space saving, suitable for taps with a low spout height: H. 63mm - Ø. 56mm

Controlled management of retro-contamination: protective skirt and angled connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 4 months after installation.

Resistance to thermal shocks: 70°C for 30 minutes.

Resistance to chemical shocks: active chlorine levels up to 100 ppm for 4 hours (cumulative total).

Sterile filter.

Packaged in boxes of 10 units.

TECHNICAL CHARACTERISTICS

BIOFIL 4-month tap and wall shower filter - Ref. 20450

Technology	Point-of-use filtration
Height	63mm
Flow rate	4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar
Diameter	56mm
Lifespan	4 months

Norms

ACS

WRAS

KTW
BWGL

CE



Anti-Legionella and all-germ



Space saving



Optimised position: angled connection



Lifespan: 4 months after installation

