

# Recessed thermostatic sequential shower mixer with angled outlet

Ref. H9633L

SECURITHERM mixer with no non-return valves, kit 2/2

2025 UK public price excluding VAT: £358.27

## DESCRIPTION

Recessed thermostatic sequential shower mixer with angled outlet - Ref. H9633L

Recessed SECURITHERM thermostatic shower with elbow outlet, kit 2/2 :  
Thermostatic sequential mixer: opens and closes with cold water.  
Mixer with no non-return valves on the inlets (reduces bacterial proliferation).  
No risk of cross flow between hot and cold water.  
Sequential mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.  
Prevents cold showers: cold water supply shuts off if hot water supply fails.  
Sequential mixer with Securitouch thermal insulation prevents burns.  
Scale-resistant thermostatic sequential cartridge adjusts the flow rate and temperature.  
Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.  
Tested without water to comply with NHS requirements. No pre-set temperature.  
Thermal shocks are possible.  
Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head.  
Hygiene lever L. 100mm.  
Filters integrated on the inlets M3/4".  
Order a shower head or wall outlet.  
Bright polished stainless steel wall plate 166 x 166mm.  
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
Sequential mixer suitable for people with reduced mobility.  
Shower mixer with 30-year warranty.  
Order the waterproof recessing housing ref. H96CBOX.

## TECHNICAL CHARACTERISTICS

Recessed thermostatic sequential shower mixer with angled outlet - Ref. H9633L

|                     |                                                                            |
|---------------------|----------------------------------------------------------------------------|
| Technology          | SECURITHERM Securitouch thermostatic sequential mixer                      |
| Height              | 166mm                                                                      |
| Width               | 166mm                                                                      |
| Flow rate           | Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head |
| Temperature limiter | Yes                                                                        |
| Finish              | Chrome-plated brass                                                        |

Norms



## ADVANTAGES



Sequential: opens/closes with cold water




Maximum hygiene: no non-return valves



SECURITHERM: optimal anti-scalding safety



Thermostatic: total temperature stability



|               |                                                                                   |
|---------------|-----------------------------------------------------------------------------------|
| Warranty      |  |
| Repairability |  |