

Recessed thermostatic sequential shower mixer with angled outlet

Ref. H9633L

SECURITHERM mixer with no non-return valves, kit 2/2

2026 UK public price excluding VAT: £332.73

DESCRIPTION

Recessed thermostatic sequential shower mixer with angled outlet - Ref. H9633L

Recessed SECURITHERM thermostatic shower with elbow outlet, kit 2/2 :
Thermostatic sequential mixer: opens and closes with cold water.
Mixer with no non-return valves on the inlets (reduces bacterial proliferation).
No risk of cross flow between hot and cold water.
Sequential mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.
Prevents cold showers: cold water supply shuts off if hot water supply fails.
Sequential mixer with Securitouch thermal insulation prevents burns.
Scale-resistant thermostatic sequential cartridge adjusts the flow rate and temperature.
Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.
Tested without water to comply with NHS requirements. No pre-set temperature.
Thermal shocks are possible.
Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head.
Hygiene lever L. 100mm.
Filters integrated on the inlets M3/4".
Order a shower head or wall outlet.
Bright polished stainless steel wall plate 166 x 166mm.
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Sequential mixer suitable for people with reduced mobility.
Shower mixer with 30-year warranty.
Order the waterproof recessing housing ref. H96CBOX.

TECHNICAL CHARACTERISTICS

Recessed thermostatic sequential shower mixer with angled outlet - Ref. H9633L

Technology	SECURITHERM Securitouch thermostatic sequential mixer
Height	166mm
Width	166mm
Flow rate	Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head
Temperature limiter	Yes
Finish	Chrome-plated brass

Norms



ADVANTAGES



Sequential: opens/closes with cold water




Maximum hygiene: no non-return valves



SECURITHERM: optimal anti-scalding safety



Thermostatic: total temperature stability



Warranty	
Repairability	