

Recessed thermostatic sequential shower mixer with angled outlet

Ref. H9633L

SECURITHERM mixer with no non-return valves, kit 2/2

2026 UK public price excluding VAT: £332.73

DESCRIPTION

Recessed thermostatic sequential shower mixer with angled outlet - Ref. **H9633L**

Recessed SECURITHERM thermostatic shower with elbow outlet, kit 2/2 : Thermostatic sequential mixer: opens and closes with cold water. Mixer with no non-return valves on the inlets (reduces bacterial proliferation). No risk of cross flow between hot and cold water. Sequential mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails. Prevents cold showers: cold water supply shuts off if hot water supply fails. Sequential mixer with Securitouch thermal insulation prevents burns. Scale-resistant thermostatic sequential cartridge adjusts the flow rate and temperature. Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C. Tested without water to comply with NHS requirements. No pre-set temperature. Thermal shocks are possible. Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head. Hygiene lever L. 100mm. Filters integrated on the inlets M3/4". Order a shower head or wall outlet. Bright polished stainless steel wall plate 166 x 166mm. Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics. Sequential mixer suitable for people with reduced mobility. Shower mixer with 30-year warranty. Order the waterproof recessing housing ref. H96CBOX.

TECHNICAL CHARACTERISTICS


Recessed thermostatic sequential shower mixer with angled outlet - Ref. **H9633L**

Technology	SECURITHERM Securitouch thermostatic sequential mixer
Height	166mm
Width	166mm
Flow rate	Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	 



ADVANTAGES

-  Sequential: opens/closes with cold water
-  Maximum hygiene: no non-return valves
-  SECURITHERM: optimal anti-scalding safety
-  Thermostatic: total temperature stability



Warranty



Repairability

