

BINOPTIC 2 electronic tap

Ref. 384110E

Mains, recessed, L. 220mm, Bluetooth®

2025 UK public price excluding VAT: £519.54




DESCRIPTION

BINOPTIC 2 electronic tap - Ref. 384110E

Recessed chrome-plated electronic basin tap:
230/6V mains supply.
Reduced-stagnation solenoid valve and electronic unit are integrated into the body of the tap.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant aerator.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Wall-mounted stainless steel tap.
Presence detection sensor at the end of the spout optimises detection.
Anti-blocking security.
Spout with smooth interior and low water volume (reduces bacterial development).
Set detection distance, duty flush and launch thermal shocks manually.
Bluetooth® version: advanced settings and operating data download via DELABIE Connect app.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC 2 electronic tap - Ref. 384110E

Supply	230/6V mains supply
Connector	M½"
Technology	Electronic
Spout length	220mm
Flow rate	3 lpm
Finish	Chrome-plated
Norms	ACS
Warranty	

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush

Easy to configure & monitor operation

