

BINOPTIC MIX 2 electronic basin mixer

Ref. 473110E

Mains supply, deck-mounted, H. 100mm, Bluetooth®

2025 UK public price excluding VAT: £601.57

DESCRIPTION

BINOPTIC MIX 2 electronic basin mixer - Ref. 473110E

Deck-mounted chrome-plated electronic basin mixer:
230/6V mains supply.
Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant aerator.
Adjustable duty flush (~60 seconds every 24 hours after the last use).
Stainless steel mixer, 100mm high for inset basins.
Active, infrared presence detection, sensor at the end of the spout optimises detection.
PEX flexibles F3/8" with filters and non-return valves
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Smooth interior spout with low water volume (limits bacterial niches).
Side temperature control with adjustable maximum temperature limiter.
Set detection distance, duty flush and launch thermal shocks manually.
Bluetooth® version: advanced settings and operating data download via DELABIE Connect app.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC MIX 2 electronic basin mixer - Ref. 473110E

Supply	230/6V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	100mm
Flow rate	3 lpm
Finish	Chrome-plated
Norms	ACS
Warranty	30 YEAR WARRANTY



ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush



Easy to configure & monitor operation

