BINOPTIC MIX 2 electronic basin mixer

Ref. 474110E

Mains, deck-mounted, H. 170mm, Bluetooth®

2024 UK public price excluding VAT: £610.58



DESCRIPTION ADV

Deck-mounted chrome-plated electronic basin mixer: 230/6V mains supply.

BINOPTIC MIX 2 electronic basin mixer - Ref. 474110E

Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm. Scale-resistant aerator.

Adjustable duty flush (~60 seconds every 24 hours after the last use). Stainless steel mixer, 170mm high for semi-recessed basins.

Active, infrared presence detection, sensor at the end of the spout optimises detection.

PEX flexibles F3/8" with filters and non-return valves

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Smooth interior spout with low water volume (limits bacterial niches). Side temperature control with adjustable maximum temperature limiter. Set duty flush and launch thermal shocks manually.

Bluetooth® version: advanced settings and operating data download via DELABIE Connect app.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Anti-bacterial proliferation duty flush




Easy to configure & monitor operation

TECHNICAL CHARACTERISTICS

BINOPTIC MIX 2 electronic basin mixer - Ref. 474110E

Supply	230/6V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	170mm
Flow rate	3 lpm
Finish	Chrome-plated
Warranty	30 g



© DELABIE