## BINOPTIC MIX 2 electronic basin mixer

Ref. 47300615

Batteries, deck-mounted, stopcocks, H. 100mm

2025 UK public price excluding VAT: £529.77



BINOPTIC MIX 2 electronic basin mixer - Ref. 47300615

Deck-mounted satin electronic basin mixer:

Operated by CR123 6V Lithium batteries.

Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm. Scale-resistant aerator.

Adjustable duty flush (~60 seconds every 24 hours after the last use). Stainless steel mixer, 100mm high for inset basins.

Presence detection sensor at the end of the spout optimises detection. PEX flexibles with stopcocks, filters, non-return valves and  $\emptyset$  15mm conical

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Smooth spout interior with low water volume (reduces bacterial development).

Side temperature control with adjustable maximum temperature limiter. Set detection distance, duty flush and launch thermal shocks manually. Suitable for people with reduced mobility. 30-year warranty.

## TECHNICAL CHARACTERISTICS

BINOPTIC MIX 2 electronic basin mixer - Ref. 47300615

| Supply      | 6V batteries |
|-------------|--------------|
| Connector   | M½" Ø 15mm   |
| Technology  | Electronic   |
| Drop height | 100mm        |
| Flow rate   | 3 lpm        |
| Finish      | Satin        |
| Warranty    | 30 g         |



## **ADVANTAGES**



Exceptional water savings: 90%




Hygiene: no manual contact



Anti-bacterial proliferation duty flush



LED diagnostic aids



© DELABIE