

BINOPTIC MIX 2 electronic basin mixer

Ref. 47400015

Mains, deck-mounted, stopcocks, H. 170mm

2025 UK public price excluding VAT: £557.09




DESCRIPTION

BINOPTIC MIX 2 electronic basin mixer - Ref. 47400015

Deck-mounted satin electronic basin mixer:
230/6V mains supply.
Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant aerator.
Adjustable duty flush (~60 seconds every 24 hours after the last use).
Stainless steel mixer, 170mm high for semi-recessed basins.
Presence detection sensor at the end of the spout optimises detection.
PEX flexibles with stopcocks, filters, non-return valves and Ø 15mm conical inlets.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Smooth spout interior with low water volume (reduces bacterial development).
Side temperature control with adjustable maximum temperature limiter.
Set detection distance, duty flush and launch thermal shocks manually.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC MIX 2 electronic basin mixer - Ref. 47400015

Supply	230/6V mains supply
Connector	M½" Ø 15mm
Technology	Electronic
Drop height	170mm
Flow rate	3 lpm
Finish	Satin
Warranty	

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush



LED diagnostic aids

