

# BINOPTIC MIX 2 electronic basin mixer

Ref. 47500015

Mains, deck-mounted, stopcocks, H. 250mm

2025 UK public price excluding VAT: £584.44

## DESCRIPTION

**BINOPTIC MIX 2 electronic basin mixer - Ref. 47500015**

Deck-mounted satin electronic basin mixer:  
230/6V mains supply.  
Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant aerator.  
Adjustable duty flush (~60 seconds every 24 hours after the last use).  
Stainless steel mixer, 250mm high for countertop basins.  
Presence detection sensor at the end of the spout optimises detection.  
PEX flexibles with stopcocks, filters, non-return valves and Ø 15mm conical inlets.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Smooth interior spout with low water volume (limits bacterial niches).  
Side temperature control with adjustable maximum temperature limiter.  
Set detection distance, duty flush and launch thermal shocks manually.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC MIX 2 electronic basin mixer - Ref. 47500015**

|             |                                                                                     |
|-------------|-------------------------------------------------------------------------------------|
| Supply      | 230/6V mains supply                                                                 |
| Connector   | M½" Ø 15mm                                                                          |
| Technology  | Electronic                                                                          |
| Drop height | 250mm                                                                               |
| Flow rate   | 3 lpm                                                                               |
| Finish      | Satin                                                                               |
| Warranty    |  |



## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush



LED diagnostic aids

