BINOPTIC MIX 2 electronic basin mixer

Ref. 47503615

Batteries, deck-mounted, stopcocks, H. 250mm

2025 UK public price excluding VAT: £652.78



BINOPTIC MIX 2 electronic basin mixer - Ref. 47503615

Deck-mounted chrome-plated matte black electronic basin mixer: Operated by CR123 Lithium 6V batteries.

Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm. Scale-resistant aerator.

Adjustable duty flush (~60 seconds every 24 hours after the last use). Stainless steel mixer, 250mm high for countertop basins.

Presence detection sensor at the end of the spout optimises detection. PEX flexibles with stopcocks, filters, non-return valves and Ø 15mm conical inlets

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Smooth spout interior with low water volume (reduces bacterial development).

Side temperature control with adjustable maximum temperature limiter. Set detection distance, duty flush and launch thermal shocks manually. Suitable for people with reduced mobility. 30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC MIX 2 electronic basin mixer - Ref. 47503615

Supply	6V batteries
Connector	M½" Ø 15mm
Technology	Electronic
Drop height	250mm
Flow rate	3 lpm
Finish	Chrome-plated matte black
Warranty	30 gg WARRANTY



ADVANTAGES



Exceptional water savings: 90%




Hygiene: no manual contact



Anti-bacterial proliferation duty flush



LED diagnostic aids



© DELABIE https://www.delabie.co.uk