

# BLACK BINOPTIC electronic tap

Ref. 379DERB

Mains supply

2026 UK public price excluding VAT: £543.84



## DESCRIPTION

### BLACK BINOPTIC electronic tap - Ref. 379DERB

Matte black cross wall electronic basin tap:  
Independent IP65 electronic control unit.  
230/12V mains supply with transformer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Active, infrared movement detection, sensor at the end of the spout optimises detection.  
Filter, solenoid valve M3/8".  
Chrome-plated solid brass body.  
Matte black chrome finish.  
Chrome-plated spout L. 205mm for cross wall installation ≤ 190mm.  
Sensor cable L.120mm, flexibles and mounting all pass through the same hole.  
Anti-blocking security.  
Spout with a smooth interior and low water volume (limits bacterial niches).  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

### BLACK BINOPTIC electronic tap - Ref. 379DERB

|               |                                                                                                                                                                                                                                                                                                                                                 |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply        | Mains supply 230/12V                                                                                                                                                                                                                                                                                                                            |
| Connector     | M3/8"                                                                                                                                                                                                                                                                                                                                           |
| Technology    | Electronic                                                                                                                                                                                                                                                                                                                                      |
| Spout length  | 205mm                                                                                                                                                                                                                                                                                                                                           |
| Flow rate     | 3 lpm                                                                                                                                                                                                                                                                                                                                           |
| Norms         |     |
| Warranty      |                                                                                                                                                                                                                                                              |
| Repairability |                                                                                                                                                                                                                                                              |

## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



LED diagnostic aid



Independent IP65 electronic control unit

