

BINOPTIC electronic basin tap

Ref. 379ENCL

Mains supply

2026 UK public price excluding VAT: £462.55



DESCRIPTION

BINOPTIC electronic basin tap - Ref. 379ENCL

Recessed electronic basin tap:

Independent IP65 electronic control unit.

230/12V mains supply with transformer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Active, infrared presence detection, sensor at the end of the spout optimises detection.

Filter and solenoid valve M3/8".

Chrome-plated brass body.

Chrome-plated spout for recessed installation.

Anti-blocking security.

Spout with smooth interior and low volume of water (limits bacterial niches).

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



LED diagnostic aid



Independent IP65 electronic control unit

TECHNICAL CHARACTERISTICS

BINOPTIC electronic basin tap - Ref. 379ENCL

| | |
|--------------|--|
| Supply | 230/12V mains supply |
| Connector | M3/8" |
| Technology | Electronic |
| Spout length | 252mm |
| Flow rate | 3 lpm |
| Norms | ACS |
| Warranty | 30 <small>YEAR</small> <small>WARRANTY</small> |

