

BINOPTIC electronic basin tap

Ref. 379ENCL

Mains supply

2026 UK public price excluding VAT: £462.55



DESCRIPTION

BINOPTIC electronic basin tap - Ref. 379ENCL

Recessed electronic basin tap:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Filter and solenoid valve M3/8".
Chrome-plated brass body.
Chrome-plated spout for recessed installation.
Anti-blocking security.
Spout with smooth interior and low volume of water (limits bacterial niches).
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC electronic basin tap - Ref. 379ENCL

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Spout length	252mm
Flow rate	3 lpm
Norms	ACS CE
Warranty	30 YEAR WARRANTY

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



LED diagnostic aid



Independent IP65 electronic control unit

