Wall-mounted sequential mechanical basin mixer

Ref. 2437

Sequential mechanical mixer with fixed spout

2025 UK public price excluding VAT: £428.99



DESCRIPTION

Wall-mounted sequential mechanical basin mixer - Ref. 2437

Wall-mounted sequential mechanical basin mixer.

Sequential over a 90° range: opens and closes with cold water.

Fixed flat under-spout, L. 200mm with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.

Securitouch thermal insulation prevents burns.

Ø 35mm ceramic cartridge.

Pre-set maximum temperature limiter.

Body and spout with smooth interiors and low water volume (reduces bacterial development).

Flow rate regulated at 5 lpm.

Hygiene lever L. 150mm.

Supplied with 2 wall-mounted STOP/CHECK connectors, M1/2" M3/4".

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Sequential: opens and closes with cold water



Maximum hygiene: manages biofilm



No non-return valves




No manual contact: Hygiene lever

TECHNICAL CHARACTERISTICS

Wall-mounted sequential mechanical basin mixer - Ref. 2437

Connector	M1/2"
Technology	Sequential mechanical mixer
Spout length	200mm
Flow rate	5 lpm
Temperature limiter	YES
Finish	Chrome-plated brass
Warranty	30 S
Repairability	50 BEPARABILITY



© DELABIE https://www.delabie.co.uk