

Wall-mounted sequential mechanical basin mixer

Ref. 2437S

Sequential mechanical mixer with fixed spout

2026 UK public price excluding VAT: £339.62



DESCRIPTION

Wall-mounted sequential mechanical basin mixer - Ref. 2437S

Wall-mounted sequential mechanical basin mixer.
Sequential over a 90° range: opens and closes with cold water.
Fixed flat under-spout, L. 200mm with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.
Securitouch thermal insulation prevents burns.
Ø 35mm ceramic cartridge.
Pre-set maximum temperature limiter.
Body and spout with smooth interiors and low water volume (reduces bacterial development).
Flow rate regulated at 5 lpm.
Hygiene lever L. 150mm.
Supplied with 2 wall-mounted standard connectors, M1/2" M3/4".
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

Wall-mounted sequential mechanical basin mixer - Ref. 2437S

Connector	M1/2"
Technology	Sequential mechanical mixer
Spout length	200mm
Flow rate	5 lpm
Temperature limiter	YES
Finish	Chrome-plated brass
Norms	
Warranty	
Repairability	

ADVANTAGES



Sequential: opens and closes with cold water



Maximum hygiene: manages biofilm



No non-return valves



No manual contact: Hygiene lever

