

Wall-mounted sequential mechanical basin mixer

Ref. 2437S

Sequential mechanical mixer with fixed spout

2026 UK public price excluding VAT: £339.62






DESCRIPTION

Wall-mounted sequential mechanical basin mixer - Ref. 2437S





Wall-mounted sequential mechanical basin mixer.
 Sequential over a 90° range: opens and closes with cold water.
 Fixed flat under-spout, L. 200mm with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.
 Securitouch thermal insulation prevents burns.
 Ø 35mm ceramic cartridge.
 Pre-set maximum temperature limiter.
 Body and spout with smooth interiors and low water volume (reduces bacterial development).
 Flow rate regulated at 5 lpm.
 Hygiene lever L. 150mm.
 Supplied with 2 wall-mounted standard connectors, M1/2" M3/4".
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

Wall-mounted sequential mechanical basin mixer - Ref. 2437S

| | |
|---------------------|--|
| Connector | M1/2" |
| Technology | Sequential mechanical mixer |
| Spout length | 200mm |
| Flow rate | 5 lpm |
| Temperature limiter | YES |
| Finish | Chrome-plated brass |
| Norms |  ACS |
| Warranty |  |
| Repairability |  |

ADVANTAGES

-  Sequential: opens and closes with cold water
-  Maximum hygiene: manages biofilm
-  No non-return valves
-  No manual contact: Hygiene lever

